

AF8750C Series Note Counter



Benefits

- ◊ 'Fail-Safe' detection systems eliminate double/half/chain notes, providing dependable count accuracy.
- ◊ New elongated feed roller system ensures distressed and varied note qualities can be handled easily.
- ◊ Selectable (On/Off) automatic DustProof Cover™ for note stacker tray reduces dust, noise and eliminates the problem of 'flying' currency.
- ◊ Two counting speeds—800 & 1,350—Ensures peak performance for all qualities of bills/documents.
- ◊ Narrow dimension size measurement prevents counting smaller and oversize denomination bills mixed together.
- ◊ High quality components give greater durability.
- ◊ Extremely quiet operation.
- ◊ Variable batch selection by 10-Key Keypad.
- ◊ Easy to use, intuitive control panel.
- ◊ Easy selection of fixed and variable batching.

Features

- ◊ Two selectable counting speeds.
- ◊ Pre-set and variable batch counting.
- ◊ Large Light Emitting Diode (LED) display.
- ◊ Electronic 'last usage' default memory system.
- ◊ Quiet operation.
- ◊ Selectable, automatic open/close DustProof Cover™ facility.
- ◊ Automatic Start.
- ◊ Batch and cumulative totalling.
- ◊ 3, 4 and 5mm size detection (in the narrow dimension).
- ◊ Count accumulation display.
- ◊ Choice of Manual or Automatic (M/A) count start mode.
- ◊ Choice of manual and automatic doubles detection settings—(Defaults to automatic at switch-on).
- ◊ Integral Self-Test and Engineering Diagnostic Software.

Options

- ◊ UV Counterfeit Detection Aid (CDA) with sensitivity adjustment and lamp monitoring.
- ◊ RS-232C Computer Interface Port.
- ◊ Remote Count Display (RCD) Unit—(The RCD Connection mounting socket is fitted as standard on all models, thus the RCD unit can be attached at a later time).
- ◊ Available without the DustProof Cover™.

Specifications

- ◊ Dimensions: 283(L) x 216(w) x 230(h)mm.
- ◊ Net Weight: 6.2kg.
- ◊ Speed: 800 and 1,350 documents per minute.
- ◊ Capacity: Hopper feed capacity to +400 notes (currency condition specific). Stacker tray capacity to 125 notes.
- ◊ Documents Range: Thickness: 0.05-0.2mm / Size: 60 x 100mm (min) to 95 x 193mm (max).
- ◊ Voltage: 110 Volts AC, or 220 Volts AC \pm 10%, at 50/60Hz. (User selectable).
- ◊ Power consumption: 50 Watts (operating).
- ◊ Ambient Temperature: 0-40° Centigrade.
- ◊ Relative Humidity: 30-75%.
- ◊ Approvals: 'CE' and 'UL'.

Shipping

- ◊ Individual Carton: 31(L) x 30(w) x 31(h)cm (0.03Cbm) at 7.5kg.
- ◊ 4 Piece Carton: 67(L) x 66(w) x 35(h)cm (0.15Cbm) at 32kg.