

AF8760C Series Note Counter



Benefits

- ◇ Automatic denomination recognition by size, provides value as well as unit count displays for quicker, more efficient processing of cash.
- ◇ Clear icon graphics and digital Liquid Crystal Display (LCD) ensures faster, more accurate set-up.
- ◇ 'Fail Safe' operating controls ensure full security through visual and audible alarms, preventing double, half, or chain note feeding and inadvertent 'rogue' or 'stranger' bank notes being included in the count.
- ◇ Denomination recognition reduces the chance of transcription or reporting errors.
- ◇ Selectable (On/Off), automatic DustProof Cover™ reduces pollution, reduces operating noise level and eliminates possible loss through 'flying' currency.

Features

- ◇ Three selectable counting speeds.
- ◇ Pre-set and variable batch counting via 10-key keypad.
- ◇ Large (8-digit) counting LCD.
- ◇ Electronic 'last usage' memory system for Function Settings and Numeric Totals.
- ◇ Automatic or Manual Start mode.
- ◇ Batch Display (3-digit LCD).
- ◇ 3, 4 & 5mm size detection (In the narrow dimension).
- ◇ Count & Value Count accumulation display.
- ◇ Integral Self-Test & Engineering Diagnostic software.

Options

- ◇ Ultraviolet (UV) Counterfeit Detection Aid (CDA) system (with sensitivity adjustment and source monitoring).
- ◇ RS-232C Computer Interface Port.
- ◇ Magnetic (MG) CDA system – For US\$ currency.
- ◇ 3D Size Detection (in the wide dimension at 3, 5, 7, 9 & 15mm) with self-learning Denomination Recognition by Size mode.
- ◇ Remote Count Display (RCD) Unit (8-digit LED).

Specifications

- ◇ Dimensions: 280(L) x 240(w) x 230(h)mm.
- ◇ Weight: 5.6kg.
- ◇ Speeds: 600, 1,000 & 1,500 documents per minute.
- ◇ Capacity: Hopper feed capacity = 400 notes.
Stacker tray capacity = 200 notes (150 in continuous count).
- ◇ Documents Range: Thickness: 0.05 – 0.2mm.
Size: 110 x 55mm (Minimum) to 190 x 100mm (Maximum).
- ◇ Voltage: 80 – 260 Volts AC at 50/60Hz.
- ◇ Noise Level: ≤79dB(A) – (Operating at High Speed).
- ◇ Power Consumption: 50 Watts (Operating).
- ◇ Ambient Temperature: 0 – 40°Centigrade.
- ◇ Relative Humidity: 30 – 75%.
- ◇ Approval: 'CE'.

Shipping

- ◇ Individual Carton: 31(L) x 30(w) x 31(h)cm (0.03Cbm) at 7.5kg.
- ◇ 4 Piece Carton: 67(L) x 66(w) x 35(h)cm (0.15Cbm) at 32kg.

AF8760C